



Safety Data Sheet

SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION

Product Name: KM #298 Asphalt Emulsion

Recommended Use: Roof Coating

Restriction on Use: None

Manufacturer:

KM Coatings Mfg.
1719 W. Buchanan Street
Phoenix, AZ 85007
(602)-253-1168

SDS Date of Preparation: 9/21/15

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

SECTION 2: HAZARDS IDENTIFICATION

Hazard Classification:

Physical	Health
Not Hazardous	Not Hazardous

Label Elements:

Not Hazardous in accordance with the Globally Harmonized System for the Classification and Labeling of Chemicals (GHS)

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS#	WT.%
Asphalt	8052-42-4	40-50%
Bentonite	1302-78-9	0-10%

The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURERS

Eyes: Immediately flush eyes with water while lifting the upper and lower lids. Get medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation develops, get medical attention. Launder clothing before re-use.

Inhalation: If symptoms develop, move to fresh air. If symptoms persist, get medical attention.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to a person who is unconscious or convulsing. If large amount is swallowed or gastrointestinal effects develop, get medical attention.

Most important symptoms/effects, acute and delayed May cause eye and skin irritation.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is not normally required.



Safety Data Sheet

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from firefighting to enter drains or water courses.

Specific Hazards Arising from the Chemical: This product is an aqueous mixture that will not burn until all water has evaporated. Residue will burn after the fire has evaporated. Combustion products may include oxides of carbon and sulfur and other asphyxiants.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate protective clothing to avoid eye and skin contact.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and Materials for Containment and Cleaning Up: Collect with inert material and place into a closable container for disposal.

SECTION 7 HANDLING and STORAGE

Precautions for Safe Handling: Avoid contact with the eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use.

Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

Storage: Store in a dry, well ventilated area. Protect from physical damage. Keep container closed when not in use.

SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

Exposure Guidelines:

INGREDIENTS	EXPOSURE LIMITS
Asphalt (as fume)	0.5 mg/m ³ TWA ACGIH TLV (as benzene-soluble aerosol)
Bentonite	5 mg/m ³ TWA OSHA PEL (respirable fraction) 15 mg/m ³ TWA OSHA PEL (total dust)

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

Respiratory Protection: If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Gloves: Rubber or other impervious gloves are recommended to prevent prolonged skin contact.

Eye Protection: Chemical safety goggles should be worn if splashing is possible.

Other Protective Equipment: Impervious clothing as needed to prevent contact.



Safety Data Sheet

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance And Odor: Black/Dark brown viscous liquid slight odor.

Boiling Point (@ 760 mmHg): >212°F (>100°C)	Freezing Point: 32°F (0°C)
Odor Threshold: Not determined	Viscosity: Not determined
Relative density (H₂O=1): 1.04	Vapor Pressure: 17.5 mmHg @ 20°C
VOC: <50 g/L (<0.42 lbs./gal)	Vapor Density (AIR=1): 5.3
Evaporation Rate: Not available	Solubility In Water: Dispersible
pH: Not available	Partition Coefficient n-Octanol/Water: Not determined
Flash Point: Not flammable Aqueous Solution	Autoignition Temperature: 626°F (330°C)
Decomposition Temperature: Not determined	Flammability (solid, gas): Not applicable
Flammable Limits: (vol % in air)	LEL – Not applicable UEL – Not applicable

SECTION 10 STABILITY and REACTIVITY

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions

Possibility of Hazardous Reactions: None known

Conditions to avoid: None known.

Incompatible materials: Avoid oxidizing agents and acids

Hazardous decomposition products: Thermal decomposition may yield oxides of carbon and sulfur and other asphyxiants.

SECTION 11 TOXICOLOGICAL INFORMATION

Eye: Contact may cause irritation with redness and tearing.

Skin: Prolonged skin contact may cause irritation and drying of the skin.

Inhalation: Inhalation of vapors may cause mucous membrane and upper respiratory tract irritation. Hydrogen sulfide will evolve from asphalt and collect in the headspace of containers. Hydrogen sulfide is irritating to the eyes and respiratory tract at low concentrations. High concentrations of hydrogen sulfide can cause respiratory arrest and death.

Ingestion: Ingestion may cause mucous membrane and gastrointestinal irritation.

Sensitization: This product is not expected to cause sensitization.

Chronic Effects:

Carcinogenicity: None of the components are listed as a carcinogen by NTP, IARC or OSHA.

Reproductive effects: None of the components have been shown to cause reproductive or developmental toxicity.

Numerical Measures of Toxicity:

Asphalt: Oral Rat LD50 - >5.0 g/kg; Skin Rabbit LD50 - > 2.0 g/kg

Bentonite: No toxicity data available.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Asphalt: 96 hr LL50 Oncorhynchus mykiss >1000 mg/L, 48 hr LL50 daphnia magna >1000 mg/L, 72 hr EL50 Pseudokirchnerella subcapitata >1000 mg/L

Bentonite: 96 hr Oncorhynchus mykiss LC50 19000 mg/L

Persistence and degradability: Asphalt is not biodegradable.

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects: No data available



Safety Data Sheet

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name: Not Regulated

UN Number: None

Hazard Class/Packing Group: None

Labels Required: None

Environmental hazards: None known

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable

Special precautions: None known

SECTION 15: REGULATORY INFORMATION

SARA Hazard Category (311/312): Not Hazardous

EPA SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

NFPA Rating:

Health = 1

Fire = 0

Instability = 0

HMIS Rating:

Health = 1

Fire = 0

Physical Hazard = 0

SDS Date of Preparation: 07/22/15

Revision Summary: New SDS.

NOTICE

The information contained herein is based upon the data available to us and is believed to be accurate. However, KM Coatings Mfg. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. KM Coatings Mfg. assumes no responsibility for injury from the use of the products described herein.

This MSDS conforms with the OSHA Hazard Communication Standard 1900.1210 and to SARA Title III, Section 313 for supplier notification.