



# Safety Data Sheet

## SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION

**Product Name:** KM-PS#220 Silicone

**Recommended Use:** Silicone Roof Coating

**Restriction on Use:** None

**Manufacturer:**

KM Coatings Mfg.  
1719 W. Buchanan Street  
Phoenix, AZ 85007  
(602)-253-1168

SDS Date of Preparation: 07/02/15

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

## SECTION 2: HAZARDS IDENTIFICATION

Physical	Health
Flammable Liquid Category 3	Skin Irritation Category 2 Specific Target Organ Toxicity – Single Exposure Category 3 (CNS) Aspiration Hazard Category 1

**Label Elements:**

**Danger!**



Flammable Liquid and vapor.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. No smoking.  
Keep container tightly closed.  
Ground and bond container and receiving equipment  
Use explosion-proof electrical, ventilating and lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing mist, vapors or spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves, eye protection and face protection.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation occurs: Get medical attention.  
Take off contaminated clothing and wash it before reuse.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER or doctor if you feel unwell.



**KM COATINGS MFG.**

# Safety Data Sheet

IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
Do NOT induce vomiting.  
In case of fire: Use foam, dry chemical, carbon dioxide or water to extinguish.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents and container in accordance with local and national regulations.

## SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS#.	WT.%
Crystalline Silica, quartz	14808-60-7	30-35%
Hydrotreated Light Petroleum Distillates	64742-47-8	10-20%

The exact percentage (concentration) of composition has been withheld as a trade secret.

## SECTION 4 FIRST AID MEASURES

**Eyes:** Flush with large quantities of water, holding the eyelids apart. Get medical attention if irritation develops.

**Skin:** Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. If irritation develops, get medical attention. Launder clothing before re-use.

**Inhalation:** Remove to fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. If breathing has stopped, administer artificial respiration. Get medical attention if symptoms develop or persist.

**Ingestion:** If conscious, rinse mouth with water. DO NOT induce vomiting. Never give anything by mouth to a person who is unconscious or convulsing. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

**Most important symptoms/effects, acute and delayed:** May cause eye irritation. Causes skin irritation with redness, itching and dryness. Inhalation of vapors or mists may cause upper respiratory tract irritation and central nervous system effects. Aspiration during swallowing or vomiting may cause lung damage.

**Indication of immediate medical attention and special treatment, if necessary:** If large amounts are swallowed, get medical attention.

## SECTION 5 FIRE FIGHTING MEASURES

**Extinguishing Media:** Use water, carbon dioxide, dry chemical or foam to extinguish fire. Do not use a water jet. Cool fire exposed containers with water.

**Special Protective Equipment and Precautions for Fire-fighters:** Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus.

**Specific Hazards Arising from the Chemical:** This product is flammable and may form explosive mixtures with air. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Closed containers may explode if exposed to extreme heat.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Wear appropriate protective clothing to avoid eye and skin contact.



# Safety Data Sheet

**Environmental precautions:** Avoid release to the environment. Report releases as required by local, state and federal authorities.

**Methods and Materials for Containment and Cleaning Up:** Dike the spilled material. Attempt to reclaim the free product, if this is possible. Collect with an inert material and place into a closable container for disposal. Use non-sparking tools and equipment. Do not flush to sewer!

**SECTION 7 HANDLING and STORAGE**

**Precautions for Safe Handling:** Avoid contact with eyes, skin and clothing. Avoid breathing aerosols, mists and heated vapors. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep product away from heat, sparks, flames and all other sources of ignition. Do not permit smoking in use or storage areas. Use with non-sparking tools and explosion proof equipment. Electrically bond and ground containers for transfer.

Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a dry, well-ventilated area away from heat, direct sunlight and all sources of ignition. Store in a tightly closed container. Avoid storing above 100°F. Keep in original container.

**SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION**

**Exposure Guidelines:**

INGREDIENTS	EXPOSURE LIMITS
Crystalline Silica, Quartz	10 mg/m <sup>3</sup> TWA OSHA PEL (respirable fraction) % Silica + 2 0.025 mg/m <sup>3</sup> TWA ACGIH TLV (respirable fraction)
Hydrotreated Light Petroleum Distillates	100 ppm TWA manufacturer recommended

**Appropriate Engineering Controls:** Use with adequate local exhaust ventilation to maintain exposures below the occupational exposure limits. Use explosion proof equipment where required.

**Respiratory Protection:** None normally required. If the exposures the product is heated or sprayed, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Gloves:** Impervious gloves are recommended to prevent skin contact.

**Eye Protection:** Chemical safety goggles recommended if contact is possible.

**Other Protective Equipment:** Impervious clothing as needed to prevent contact.

**SECTION 9 PHYSICAL and CHEMICAL PROPERTIES**

**Appearance And Odor:** Colored viscous liquid with a petroleum odor.

<b>Boiling Point (@ 760 mmHg):</b> 310-385°F / 154.4-196.1°C	<b>Freezing Point:</b> Not available
<b>Odor Threshold:</b> Not available	<b>Viscosity:</b> Not available
<b>Relative density (H2O=1):</b> 1.23	<b>Vapor Pressure:</b> Not available
<b>VOC:</b> <250 g/L	<b>Vapor Density (AIR=1):</b> >1
<b>Evaporation Rate:</b> Slower than ether	<b>Solubility In Water:</b> Negligible
<b>pH:</b> Not available	<b>Partition Coefficient n-Octanol/Water:</b> Not determined
<b>Flash Point:</b> >108°F / >42.2°C COC	<b>Autoignition Temperature:</b> Not available
<b>Decomposition Temperature:</b> Not available	<b>Flammability (solid, gas):</b> Not applicable



KM COATINGS MFG.

## Safety Data Sheet

Flammable Limits: (vol % in air) LEL – N/A UEL – N/A

### SECTION 10 STABILITY and REACTIVITY

**Reactivity:** Not normally reactive.

**Chemical Stability:** Stable under normal storage and handling conditions

**Possibility of Hazardous Reactions:** None known

**Conditions to avoid:** Excessive heat.

**Incompatible materials:** Avoid strong oxidizing agents, acids, halogens and molten sulfur.

**Hazardous decomposition products:** Thermal decomposition may yield oxides of carbon and nitrogen and hydrocarbons.

### SECTION 11 TOXICOLOGICAL INFORMATION

**Eye:** Contact may cause irritation with redness, pain and tearing.

**Skin:** Skin contact may cause irritation with redness, itching and drying of the skin.

**Inhalation** Inhalation of vapors or mists may cause mucous membrane and upper respiratory irritation, headache, dizziness, drowsiness, weakness, fatigue and central nervous system effects.

**Ingestion:** Ingestion may cause gastrointestinal irritation, nausea and diarrhea. Aspiration during swallowing or vomiting may cause lung damage.

**Sensitization:** None of the components have been shown to cause sensitization in animals or humans.

**Chronic Effects:** None known.

**Carcinogenicity:** Crystalline silica quartz is listed as "Carcinogenic to Humans" (Group 1) by IARC and "Known to be a Human Carcinogen" by NTP. The crystalline silica, quartz is inextricably bound and no exposure occurs during use. None of the other components present at 0.1% or greater are listed as a carcinogen by NTP, IARC, ACGIH or OSHA.

**Numerical Measures of Toxicity:**

Crystalline Silica, Quartz: Oral rat LD50 >22,500 mg/kg

Hydrotreated Light Petroleum Distillates: Oral rat LD50 > 5000 mg/kg; Inhalation rat LC50 > 5.28 mg/L/4 hr; Dermal rabbit LD50 > 2000 mg/kg

### SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity:**

Crystalline Silica: 72 hr LC50 carp >10,000 mg/L

Hydrotreated Light Petroleum Distillates: 96 hr LC50 Oncorhynchus mykiss 2 mg/L; 48 hr EC50 Daphnia magna EC50 1.4 mg/L; 72 hr EC50 Pseudokirchnerella subcapitata 1 mg/L

**Persistence and degradability:** Biodegradation is not applicable to inorganic substances such as crystalline silica, quartz.

**Bioaccumulative potential:** No data available.

**Mobility in soil:** No data available.

**Other adverse effects:** No data available.

### SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose in accordance with all local, state and federal regulations.

### SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name: Excepted from HazMat (49 CFR 173.150(f))

UN Number: None



# Safety Data Sheet

Hazard Class/Packing Group: None  
Labels Required: None

**Environmental hazards:** None known

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form.

**Special precautions:** None known

**SECTION 15: REGULATORY INFORMATION**

**SARA Hazard Category (311/312):** Acute Health, Fire Hazard

**EPA SARA 313:** This product contains the following chemicals regulated under SARA Title III, section 313: None

**CERCLA Hazardous Substances (Section 103)/RQ:** This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**Toxic Substances Control Act:** All of the components of this product are listed on the TSCA inventory.

**California Proposition 65:** This product contains the following chemical known to the State of California to cause cancer or reproductive toxicity: none – crystalline silica, quartz is inextricably bound

**WHMIS Classification:** Class B, Division 2; Class D, Division 2B

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

**SECTION 16: OTHER INFORMATION**

<b>NFPA Rating:</b>	Health = 2	Fire = 2	Instability = 0
<b>HMIS Rating:</b>	Health = 2	Fire = 2	Physical Hazard = 0

**SDS Date of Preparation:** 07/02/15

**Revision Summary:** New SDS.

### NOTICE

The information contained herein is based upon the data available to us and is believed to be accurate. However, KM Coatings Mfg. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. KM Coatings Mfg. assumes no responsibility for injury from the use of the products described herein.

This SDS conforms with the OSHA Hazard Communication Standard 1900.1210 and to SARA Title III, Section 313 for supplier notification.